

AWG/Metric Conductor Table

AWG	Stranding	Approx OD		Area		Weight		DC Resistance (Bare)*		DC Resistance (Tinned)*	
		Inch	mm	CMA	mm ²	Lb/1000 ft	kg/km	Ohms/1000 ft	Ohms/km	Ohms/1000 ft	Ohms/km
38	Solid	0.0040	0.102	16.0	0.008	0.048	0.071	648	2126	696	2283
38	7/46	0.0047	0.119	17.2	0.009	0.053	0.079	614	2014	659	2162
36	Solid	0.0050	0.127	25.0	0.013	0.076	0.113	415	1362	445	1460
36	7/44	0.0060	0.152	28.0	0.014	0.086	0.128	378	1240	406	1332
34	Solid	0.0063	0.160	39.7	0.020	0.120	0.179	261	856	280	919
34	7/42	0.0075	0.191	43.8	0.022	0.135	0.201	242	794	260	853
32	Solid	0.0080	0.203	64.0	0.032	0.194	0.289	162	531	174	571
32	7/40	0.0093	0.236	67.3	0.034	0.208	0.310	157	515	169	554
32	19/44	0.0100	0.254	76.0	0.039	0.235	0.350	139	456	149	489
30	Solid	0.0100	0.254	100	0.051	0.303	0.451	104	341	111	364
30	7/38	0.0120	0.305	112	0.057	0.346	0.515	94.5	310	101	331
30	19/42	0.0125	0.318	119	0.060	0.367	0.546	89.1	292	95.6	314
28	Solid	0.0126	0.320	159	0.081	0.481	0.716	65.2	214	69.3	227
28	7/36	0.0150	0.381	175	0.089	0.540	0.804	60.4	198	64.9	213
28	19/40	0.0155	0.394	183	0.093	0.564	0.839	57.9	190	62.2	204
27	7/35	0.017	0.432	220	0.111	0.679	1.01	48.1	158	51.7	170
26	Solid	0.0159	0.404	253	0.128	0.766	1.14	41.0	135	43.5	143
26	7/34	0.019	0.483	278	0.141	0.858	1.28	38.1	125	40.9	134
26	10/36	0.019	0.483	250	0.127	0.772	1.15	42.3	139	45.4	149
26	19/38	0.020	0.508	304	0.154	0.939	1.40	34.8	114	37.4	123
25	7/0067	0.020	0.508	314	0.159	0.970	1.44	33.7	111	36.1	118
25	7/33	0.021	0.533	353	0.179	1.09	1.62	30.0	98.4	32.2	106
25	40/40	0.023	0.584	384	0.195	1.19	1.77	27.5	90.2	29.5	96.8
24	Solid	0.0201	0.511	404	0.205	1.22	1.82	25.7	84.3	26.7	87.6
24	7/32	0.024	0.610	448	0.227	1.38	2.05	23.6	77.4	25.3	83.0
24	10/34	0.023	0.584	397	0.201	1.23	1.83	26.6	87.3	28.6	93.8
24	19/36	0.025	0.635	475	0.241	1.47	2.19	22.3	73.2	23.9	78.4
22	Solid	0.0253	0.643	640	0.324	1.94	2.89	16.2	53.1	16.9	55.4
22	7/0096	0.029	0.737	645	0.327	1.99	2.96	16.4	53.8	17.6	57.7
22	7/30	0.030	0.762	700	0.355	2.16	3.21	15.1	49.5	16.2	53.1
22	16/34	0.030	0.762	635	0.322	1.96	2.92	16.7	54.8	17.9	58.7
22	19/34	0.0315	0.800	754	0.382	2.33	3.47	14.0	45.9	15.1	49.5
20	Solid	0.032	0.813	1024	0.519	3.10	4.61	10.1	33.1	10.5	34.4
20	7/0121	0.036	0.914	1022	0.518	3.16	4.70	10.4	34.1	11.0	36.1
20	7/28	0.038	0.965	1113	0.564	3.44	5.12	9.5	31.2	10.1	33.1
20	10/30	0.037	0.940	1000	0.507	3.09	4.60	10.6	34.8	11.4	37.4
20	19/32	0.040	1.016	1216	0.616	3.75	5.58	8.7	28.5	9.3	30.6
20	26/34	0.038	0.965	1032	0.523	3.19	4.75	10.2	33.5	11.0	36.1
20	41/36	0.037	0.940	1025	0.519	3.16	4.70	10.3	33.8	11.1	36.4
20	63(7x9)/38	0.040	1.016	1008	0.511	3.17	4.72	10.7	35.1	11.5	37.7

*Nominal resistance at 20°C.

AWG/Metric Conductor Table

AWG	Stranding	Approx OD		Area		Weight		DC Resistance (Bare)*		DC Resistance (Tinned)*	
		Inch	mm	CMA	mm ²	Lb/1000 ft	kg/km	Ohms/1000 ft	Ohms/km	Ohms/1000 ft	Ohms/km
18	Solid	0.040	1.016	1624	0.823	4.92	7.32	6.39	21.0	6.64	21.8
18	7/.0152	0.046	1.168	1617	0.819	4.99	7.43	6.54	21.5	6.95	22.8
18	7/26	0.048	1.219	1771	0.897	5.47	8.14	5.97	19.6	6.34	20.8
18	16/30	0.047	1.194	1600	0.811	4.94	7.35	6.61	21.7	7.10	23.3
18	19/30	0.050	1.270	1900	0.963	5.87	8.74	5.57	18.3	5.98	19.6
18	41/34	0.047	1.194	1628	0.825	5.03	7.49	6.50	21.3	6.98	22.9
18	65/36	0.047	1.194	1625	0.823	5.02	7.47	6.51	21.4	6.99	22.9
18	105(7x15)/38	0.052	1.321	1680	0.851	5.29	7.87	6.42	21.1	6.89	22.6
16	Solid	0.051	1.295	2581	1.31	7.81	11.62	4.02	13.2	4.18	13.7
16	7/.0192	0.058	1.473	2583	1.31	7.98	11.88	4.10	13.5	4.35	14.3
16	7/24	0.060	1.524	2828	1.43	8.73	12.99	3.74	12.3	3.89	12.8
16	19/.0117	0.059	1.499	2603	1.32	8.04	11.96	4.06	13.3	4.32	14.2
16	19/29	0.057	1.448	2432	1.23	7.51	11.18	4.35	14.3	4.62	15.2
16	26/30	0.060	1.524	2600	1.32	8.03	11.95	4.07	13.4	4.37	14.3
16	65/34	0.059	1.499	2580	1.31	7.97	11.86	4.10	13.5	4.40	14.4
16	168(7x24)/38	0.067	1.702	2688	1.36	8.46	12.59	4.01	13.2	4.31	14.1
14	Solid	0.064	1.626	4109	2.08	12.4	18.45	2.52	8.27	2.62	8.60
14	7/22	0.076	1.930	4480	2.27	13.8	20.53	2.36	7.74	2.46	8.07
14	7/.0242	0.073	1.854	4102	2.08	12.7	18.90	2.58	8.46	2.68	8.79
14	19/.0147	0.074	1.880	4104	2.08	12.7	18.90	2.58	8.46	2.74	8.99
14	19/27	0.071	1.803	3838	1.94	11.8	17.56	2.76	9.06	2.93	9.61
14	41/30	0.074	1.880	4100	2.08	12.7	18.90	2.58	8.46	2.77	9.09
14	105/34	0.075	1.905	4168	2.11	12.9	19.20	2.54	8.33	2.72	8.92
14	266(7x38)/38	0.080	2.032	4256	2.16	13.4	19.94	2.53	8.30	2.72	8.92
12	Solid	0.081	2.057	6529	3.31	19.8	29.47	1.59	5.22	1.65	5.41
12	7/20	0.096	2.438	7168	3.63	22.1	32.88	1.48	4.85	1.53	5.02
12	7/.0305	0.092	2.337	6510	3.30	20.1	29.91	1.62	5.31	1.69	5.54
12	19/.0185	0.093	2.362	6498	3.29	20.1	29.91	1.63	5.35	1.73	5.68
12	19/25	0.090	2.286	6080	3.08	18.8	27.98	1.74	5.71	1.85	6.07
12	65/30	0.093	2.362	6500	3.29	20.1	29.91	1.63	5.35	1.75	5.74
12	168(7x24)/34	0.106	2.692	6670	3.38	21.0	31.25	1.62	5.31	1.74	5.71
12	413(7x59)/38	0.106	2.692	6608	3.35	20.8	30.95	1.63	5.35	1.75	5.74
10	Solid	0.102	2.591	10384	5.26	31.4	46.73	0.999	3.28	1.04	3.41
10	7/.0385	0.116	2.946	10374	5.26	32.0	47.62	1.02	3.35	1.06	3.48
10	19/.0234	0.117	2.972	10412	5.28	32.1	47.77	1.02	3.35	1.06	3.48
10	19/23	0.113	2.870	9709	4.92	30.0	44.64	1.09	3.58	1.13	3.71
10	37/.0167	0.117	2.972	10323	5.23	31.9	47.47	1.02	3.35	1.09	3.58
10	37/26	0.111	2.819	9361	4.74	28.9	43.01	1.13	3.71	1.20	3.94
10	105/30	0.118	2.997	10500	5.32	32.4	48.22	1.01	3.31	1.08	3.54
10	658(7x94)/38	0.132	3.353	10528	5.33	33.1	49.26	1.02	3.35	1.10	3.61

*Nominal resistance at 20°C.

AWG/Metric Conductor Table

AWG	Stranding	Approx OD		Area		Weight		DC Resistance (Bare)*		DC Resistance (Tinned)*	
		Inch	mm	CMA	mm ²	Lb/1000 ft	kg/km	Ohms/1000 ft	Ohms/km	Ohms/1000 ft	Ohms/km
8	Solid	0.129	3.277	16512	8.37	50.0	74.41	0.628	2.06	0.646	2.12
8	19/.0295	0.148	3.759	16530	8.38	51.0	75.90	0.640	2.10	0.665	2.18
8	19/21	0.143	3.632	15428	7.82	47.6	70.84	0.686	2.25	0.713	2.34
8	49(7x7)/.0184	0.166	4.216	16611	8.42	52.3	77.83	0.649	2.13	0.690	2.26
8	65/26	0.148	3.759	16445	8.33	50.8	75.60	0.643	2.11	0.683	2.24
8	133(7x19)/29	0.169	4.293	17024	8.63	53.6	79.77	0.634	2.08	0.673	2.21
8	168(7x24)/30	0.167	4.242	16800	8.51	52.9	78.72	0.642	2.11	0.689	2.26
8	266(7x38)/32	0.166	4.216	17024	8.63	53.6	79.77	0.634	2.08	0.680	2.23
6	19/.0372	0.186	4.724	26296	13.3	81.2	120.84	0.402	1.32	0.418	1.37
6	19/19	0.180	4.572	24491	12.4	75.6	112.51	0.432	1.42	0.449	1.47
6	37/23	0.158	4.013	18907	9.58	58.4	86.91	0.559	1.83	0.582	1.91
6	49(7x7)/.0231	0.208	5.283	26166	13.3	81.6	121.43	0.408	1.34	0.425	1.39
6	105/26	0.188	4.775	26565	13.5	82.0	122.03	0.398	1.31	0.423	1.39
6	133(7x19)/27	0.213	5.410	26866	13.6	84.6	125.90	0.401	1.32	0.426	1.40
6	266(7x38)/30	0.210	5.334	26600	13.5	83.7	124.56	0.405	1.33	0.435	1.43
6	413(7x59)/32	0.212	5.385	26432	13.4	83.2	123.82	0.408	1.34	0.438	1.44
4	19/.0469	0.235	5.969	41800	21.2	129	191.97	0.253	0.830	0.263	0.863
4	49(7x7)/.0292	0.263	6.680	41797	21.2	130	193.46	0.256	0.840	0.266	0.873
4	133(7x19)/25	0.269	6.833	42560	21.6	134	199.41	0.253	0.830	0.269	0.883
4	168(7x24)/26	0.266	6.756	42504	21.5	134	199.41	0.254	0.833	0.270	0.886
4	413(7x59)//30	0.265	6.731	41300	20.9	130	193.46	0.261	0.856	0.280	0.919
4	420(7x60)/30	0.268	6.807	42000	21.3	132	196.44	0.257	0.843	0.276	0.906
4	665(19x35)/32	0.270	6.858	42560	21.6	134	199.41	0.253	0.830	0.272	0.892
2	19/.0591	0.296	7.518	66367	33.6	205	305.07	0.159	0.522	0.166	0.545
2	133(7x19)/23	0.339	8.611	67963	34.4	214	318.47	0.159	0.522	0.165	0.541
2	259(7x37)/26	0.334	8.484	65527	33.2	207	308.05	0.165	0.541	0.176	0.577
2	266(7x38)/26	0.334	8.484	67298	34.1	212	315.49	0.160	0.525	0.170	0.558
2	665 (7x95)/30	0.336	8.534	66500	33.7	209	311.03	0.162	0.531	0.174	0.571
2	665(19x35)/30	0.338	8.585	66500	33.7	209	311.03	0.162	0.531	0.174	0.571
2	1045(19x55)/32	0.342	8.687	66880	33.9	213	316.98	0.163	0.535	0.175	0.574
1	19/.0664	0.332	8.433	83771	42.4	259	385.43	0.126	0.413	0.131	0.430
1	133(7x19)/22	0.380	9.652	85120	43.1	268	398.83	0.127	0.417	0.132	0.433
1	259(7x37)/25	0.376	9.550	82880	42.0	262	389.90	0.131	0.430	0.139	0.456
1	836(19x44)/30	0.383	9.728	83600	42.4	266	395.85	0.130	0.427	0.140	0.459
1/0	19/.0745	0.373	9.474	105450	53.4	326	485.14	0.100	0.328	0.104	0.341
1/0	133(7x19)/21	0.428	10.871	107996	54.7	340	505.98	0.100	0.328	0.104	0.341
1/0	259(7x37)/24	0.422	10.719	104636	53.0	331	492.58	0.104	0.341	0.108	0.354
1/0	1045(19x55)/30	0.428	10.871	104500	53.0	332	494.07	0.104	0.341	0.112	0.367
1/0	1064(19x56)/30	0.430	10.922	106400	53.9	338	503.00	0.102	0.335	0.110	0.361
2/0	19/.0837	0.419	10.643	133114	67.4	411	611.64	0.079	0.259	0.083	0.272
2/0	133(7x19)/20	0.480	12.192	136192	69.0	429	638.42	0.079	0.259	0.082	0.269
2/0	259(7x37)23	0.474	12.040	132349	67.1	419	623.54	0.082	0.269	0.085	0.279
2/0	1323(7x7x27)/30	0.539	13.691	132300	67.0	424	630.98	0.083	0.272	0.089	0.292
2/0	1330(19x70)/30	0.483	12.268	133000	67.4	427	635.45	0.083	0.272	0.089	0.292

*Nominal resistance at 20°C.